

**NEW**



## CLEARs FROM 1¼" TO 4" (32 - 100 mm) DRAIN LINES

RIDGID FlexShaft machines are lightweight, compact and highly efficient machines that deliver wall-to-wall clean in 1¼" to 4" (32 to 100 mm) drain lines up to 70' (21,3m).

FlexShaft machines can also be operated while an inspection camera is in the line letting you see while you clean. No other soft blockage expert can do that.

- ▶ **WALL-TO-WALL CLEAN**  
Chain knockers expand for full pipe cleaning
- ▶ **SIMULTANEOUS CAMERA USE**  
FlexShaft machines let you keep your camera in-pipe while you work
- ▶ **INCREASE PRODUCTIVITY**  
Faster setup and cleanup, quick cleaning, and cordless convenience for additional time savings
- ▶ **CUSTOMIZE YOUR MACHINE**  
A full range of chain knockers and accessories are available



RIDGID® FlexShaft machines utilize specialized chain knockers attached to a flexible cable that are spun at high speeds by a cordless drill with an adjustable clutch (not included) attached to the center drive shaft. Since the cable spins inside a durable nylon sheath that is housed within a fully contained drum, there is less jobsite mess.



## SPECIFICATIONS

Model.....	K9-102 .....	K9-204 .....
Drain Capacity .....	1¼" to 2" (32 - 50 mm).....	2" to 4" (50 - 100 mm)
Cable Diameter (without Sheath) .....	¼" (6 mm).....	⅝" (8 mm)
Cable Assy. Diameter (with Sheath) .....	⅜" (9,5 mm) .....	½" (12,7 mm)
Cable Assembly Length.....	50' (15,2 m).....	70' (21,3 m)
Rotational Speed.....	Maximum 2500 RPM.....	Maximum 2500 RPM
Drill Attachment* .....	⅝" Hex (8 mm).....	⅝" Hex (8 mm)
Weight (without Drill/Knocker).....	24.3 lbs. (11,0 kg).....	38.2 lbs. (17,3 kg)
Dimension (without Drill) .....	19,2" x 7,5" x 22,1".....	21,1" x 10,8" x 24,2"
	(488 mm x 191 mm x 562 mm).....	(536 mm x 274 mm x 615 mm)
Operating temperature.....	-6°C to 60°C.....	-6°C to 60°C

\*Drill not included

## ORDER INFORMATION

Cat. N°	Model	Description	Weight Kg
64268	K9-102 GLOBAL	FlexShaft, 1¼" to 2" (32 - 50 mm) Includes: 50' (15,2 m) of ¼" (6 mm) cable and kit*	13,4
64278	K9-204 GLOBAL	FlexShaft, 2" to 4" (50 - 100 mm) Includes: 70' (21,3 m) of ⅝" (8 mm) cable and kit**	20,1

\* K9-102 includes: K9-102 1½" & K9-102 2" Knockers, FlexShaft 4 oz (118 ml) Lubricant, PVC 1¼" & PVC 1½" Attachments, Hex Key 4 mm T-handle Tool, Hex Key 3 mm T-handle Tool, RIDGID Tool Bag, K9-102 & K9-204 Manual Pack.

\*\* K9-204 includes: K9-204 2" & K9-204 4" Knockers, FlexShaft 4 oz (118 ml) Lubricant, Hex Key 4 mm T-handle Tool, Hex Key 3 mm T-handle Tool, RIDGID Tool Bag, K9-102 & K9-204 Manual Pack.

## ACCESSORIES

Cat. N°	Description
64283	FlexShaft Knocker, ¼" (6 mm) cable, 1¼" - 2" (32 - 50 mm) pipe, single chain, carbide tip
64288	FlexShaft Knocker, ¼" (6 mm) cable, 2" (50 mm) pipe, 2 chain, carbide tip
64293	FlexShaft Knocker, ¼" (6 mm) cable, 1¼"-2" (32 - 50 mm) pipe, single chain
64298	FlexShaft Knocker, ¼" (6 mm) cable, 2" (50 mm) pipe, 2 chain
64308	FlexShaft Knocker, ⅝" (8 mm) cable, 2" (50 mm) pipe, 2 chain, carbide tip
64313	FlexShaft Knocker, ⅝" (8 mm) cable, 3" (75 mm) pipe, 3 chain, carbide tip
64318	FlexShaft Knocker, ⅝" (8 mm) cable, 4" (100 mm) pipe, 3 chain, carbide tip
64323	FlexShaft Knocker, ⅝" (8 mm) cable, 2" (50 mm) pipe, 2 chain
64328	FlexShaft Knocker, ⅝" (8 mm) cable, 3" (75 mm) pipe, 3 chain
64333	FlexShaft Knocker, ⅝" (8 mm) cable, 4" (100 mm) pipe, 3 chain
64338	RIDGID FlexShaft Lubricant, 8 oz (238 ml), 12 per case
64343	FlexShaft ¼" (6 mm) Assembly, cable, sheath, couplings 50' (15,2 m)
64348	FlexShaft ⅝" (8 mm) Assembly, cable, sheath, couplings 70' (21,3 m)



RIDGID® reserves the right to change design and specification of our products without notification or alteration of literature. For the complete selection of the Ridge Tool product line, please refer to the RIDGID® Tool Catalog or [RIDGID.com](http://RIDGID.com).

© 2018 RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries. All other trademarks belong to their respective holders.



Chain Knockers

- All pipe types
- For soft blockages and grease



Carbide Tipped Chain Knockers

- Hard walled pipes
- For soft blockages, grease, scale and roots



For more details visit [RIDGID.com/warranty](http://RIDGID.com/warranty)

## DISTRIBUTOR

**RIDGID**

Ridge Tool Europe N.V.  
Ondernemerslaan 5428  
3800 Sint-Truiden, Belgium

Tel.: +32 (0)11 598 620  
[ridgid.benelux@emerson.com](mailto:ridgid.benelux@emerson.com)  
RIDGID.com

**EMERSON**