



**NEW!**



## SeeSnake® nanoReel Industrial Inspection Camera System

The SeeSnake® nanoReel® opens up new possibilities in long run small diameter inspection needs.

Applications where only bore scopes could reach can now be inspected using the nanoReel®. Boiler tubes, supply lines, sprinkler systems, and a wide array of specialty applications can all be inspected using the new nanoReel®.

- **Small diameter** and **tight turn** radius camera allows lines up to 25m to be inspected with tight turns in 25 mm lines. The camera passes 90° bends from 30mm onwards in most pipes (depends on the conditions and pipe construction, this cannot be guaranteed).
- **Lightweight** and **compact** unit allows for easy transport and efficient storage.
- Connects to the micro CA-300 or any SeeSnake® monitor.
- **Interchangeable drums** let you change out the inner drum depending on the application. See the RIDGID® small diameter inspection reels selection on the next page.

Camera Head.....	0.62 (15.5 mm)
Cable Length.....	85' (25 m)
Cable Diameter.....	0.25 (6.3 mm)
Line Capacity.....	3/4" to 2" (25 to 50 mm)
Weight.....	9.5 lbs. (4.1 kg)
Length.....	13.25" (33.7 cm)
Width.....	6.6" (16.8 cm)
Height.....	17.5" (44.5 cm)
Resolution.....	510 x 496 PAL
Ball Guide.....	2 Included
Sonde.....	512 Hz
Counter.....	NA

Ordering Information (reel only)	
40003	nanoReel® for micro CA-300
40013	nanoReel® for SeeSnake®



# Inspection Camera Systems: Selection Overview

## Overview of the RIDGID® small diameter inspection reels.



	nanoReel	microDrain	microDrain Sonde	microReel	microReel Counter
<b>For pipes diameter <sup>(1)</sup>:</b>	25-50mm	30-100mm	30-100mm	40-125mm	40-125mm
Camera Head	15.5 mm	22 mm	22 mm	25 mm	25 mm
Passes 90° bends from	30mm	40mm	40mm	50mm	50mm
Pushcable length	25m	10m	20m	30m	30m
Cable Diameter	6.3mm (flexible)	8.3mm (flexible)	8.3mm (flexible)	6.7mm (stiff)	6.7mm (stiff)
Locating sonde (512Hz)	Standard	-	Standard	Standard	Standard
Sonde power	Low	-	Low	Medium	Medium
Meter counter	-	-	-	-	Standard
Applications	Boiler tube inspection Supply line inspection Sprinkler plumbing inspection Small diameter drains	Pools (90° bends from 40mm onwards) Toilet traps Sink traps Small diameter drains		Sewer laterals Chimneys Floor drains General drain inspection	
Reel connects to <sup>(2)</sup> :					
- Any SeeSnake® monitor	•	•	•	•	•
- micro CA-300	•	•	•	•	•

(1) capacity stated when using a SeeSnake® monitor.  
(2) given you use the correct type interconnect cord.



## Monitors that connect to our reels



	micro CA-300	MiniPak	CS10	LT1000M Laptop Interface
Screen Size	3,5" LCD	5,7" LCD	12,1" LCD	Depends on laptop used
Recording	Digital	-	Digital	Depends on laptop used
Operates with battery	3,7V Li	18V Li	1 or 2 18V Li	18V Li
Operates on 230V	Yes	Yes	Yes	Yes
Includes SeeSnake® reporting software	-	-	Yes	Yes
USB connection	Yes	-	Yes	Yes
Catalog number:				
- Including battery kit	40613	32953	39343	36668
- Monitor only	-	32688	39333	36658



**For the complete selection of the Ridge Tool product line, please refer to the Ridge Tool Catalog or [www.RIDGID.eu](http://www.RIDGID.eu).**

### DISTRIBUTOR



Units 16/17 Mill Road Industrial Estate  
Radstock  
Somerset  
BA3 5TX

Tel: 01761-432041  
Fax: 01761-432042  
Email: [sales@dartsystems.co.uk](mailto:sales@dartsystems.co.uk)

RIDGID® reserves the right to change design and specification of our products without notification or alteration of literature.



Ridge Tool UK  
c/o Emerson Electric UK Limited 2nd  
Floor Accurist House  
44 Baker Street  
London  
W1U 7AL

T: +44 (0) 808 238 9869 UK  
F: +44 (0) 808 238 9904 UK  
T: +353 1 800 936 397 Ireland  
F: +353 1 800 936 240 Ireland  
[ridgid.gb@emerson.com](mailto:ridgid.gb@emerson.com)  
[www.ridgid.eu](http://www.ridgid.eu)



FY11 13BM\_UK