

Endoscopes & Inspection cameras

ME LCD SD Card Articulating Endoscope.



This Palm sized LCD Monitor style Endoscope is equipped with a LED light source, TFT Display, camera and recorder, in a compact package allowing work to be carried out quickly and easily, without the need for separate laptops / monitors or other recording systems. It also enables team discussion while outputting the image to a TV monitor, and allows better communication with the customer.

The Endoscope has an articulating tip of greater than 110° for 1m & 2m units and 90° for the 3m unit and a manually rotating neck through 330° which gives greater control to the user. The unit comes with a 1m, 2m or 3m flexible cable.

Portable Product

You can probe with the palm sized system anytime or anyplace. There's no longer any need for dragging around the luggage sized borescopes.

Long Duty Cycle

Equipped with a high capacity battery. It can record for 5 hours continuously after being charged for 2 hours. The 2GB memory card can also hold over 15,000 photos.

Features:

- 5.5mm External Diameter can easily get through spark plug holes of any gasoline or diesel engine. Extra wide angle camera can take 640 x 480 resolution pictures. 90° viewing cable available in 5.5mm dia.
- 4 Super strength fully adjustable white LED lights allow every detail to be illuminated;
- Snap Shot function, Screen image rotation, Zoom In/ Zoom Out, Photo Comparison;
- Oil and scratch resistant tempered glass not only protects the camera, but also maintains the high image resolution.
- Replacement cables available. You can install different lens modules (Range available 1m. 2m or 3m.

Contents:

Palm LCD Endoscope, Flexible Cable, Mini USB Cable, Battery Charger, 2GB Memory Card, Instruction Manual, AV Leads, Aluminium Transit Case.

System Specification:

Image Sensor CMOS Image Sensor Resolution (Dynamic / Static) 640(H)

*480(V)/640(H)*480(V)

Tube Diameter 5.5mm

Tube Length 1m, 2m or 3m

Frame Rate 30fps S/N Ratio 42db Exposure Automatic

White Balance Fix Field of View 67°

Depth of Field 1.5cm – 10cm Light Source 4 White LED

Power DC5V

Display 3.5" TFT LCD Monitor

640*480 pixels

Working Temperature -20C to 60C

Interface Mini USB 1.1/ AV out Battery Rechargeable Li-Polymer

Battery (3.7V)

Video out Format NTSC & PAL

Recording Medium SD card (the capacity can be

up to 32GB)

Compression Format MPEG4

Still Image Format JPEG (640*480)

Video Recording Format ASF (640*480)

Language English
Cable Waterproof rated to IP67

Hand Unit Dimensions 117.5mm x 37mm x 207mm



OR Code V27/09/13