

Pipe Tracer - Pipe Tracing Rod



The Dart Systems Pipe Tracer (Flexitrace) provides a lightweight and compact solution for locating ducts, pipes and drains.

The unit can easily be transported and deployed by one person and provides an alternative to traditional pipe location techniques using a Cobra Rod / Duct Rod's and a Sonde Transmitter for the location of plastic pipes, pipe / duct obstructions or collapses.

Sonde Location

Feed the rod into the duct and attach a Signal Generator to both terminals of the unit, this energises the end coil housing and allows it to be located as a traditional Sonde using a Cable Avoiding Tool.

Line Location

Feed the rod into the duct and attach a Signal Generator to one terminal of the unit and the other terminal to an earth stake. The Rod can then be located along its whole length with a Cable Avoiding Tool.

Features

- Allows the detection, location and determination of depth for buried non-metallic pipes and ducts to a depth of 3 Mtrs
- Locate either the whole path of the pipe or only locate the tip of the Sonde.
- Works in pipes and ducts with a diameter as small as 12 mm Diameter
- Works with standard Signal Generator and C.A.T. (Cable Avoiding Tool)
- Manual brake fitted to maintain control of the rod
- No batteries required
- Lightweight and compact

Construction

Rod Diameter:	4.5mm
Sonde Dimensions:	9mm Dia x 75mm
Depth Range:	Up to 3 Mtr depending on pipe construction and soil conditions.
Construction:	Glass Fibre Rod and copper conductors in a polypropylene sheath on a steel frame.
Frame Dimensions:	540mm x 400mm x 150mm
Warranty:	12 Months

Part Number	Rod Length	Rod Diameter	Core Diameter	Min Bend Radius	Weight
300-30	30 M	4.5mm	3mm	300mm	4kg
300-50	50 M	4.5mm	3mm	300mm	5kg
300-80	80 M	4.5mm	3mm	300mm	6kg